



## Description

The PA-100 is an automatic label printer/applicator that quickly and reliably prints and applies labels to flat surfaces on boxes and other products such as vacuum sealed meats. Built for durability and longevity, the PA-100 is simple to use and easy to maintain. Available with a wide variety of printer types and label sizes.

## Applications

- In-motion automatic labeling of boxes
- In-motion printing and application of catchweight labels
- In-motion automatic labeling of semi-flat objects (e.g. wrapped hams)



## Features

- Tamp and blow design ensures the label gets applied even if the item is not perfectly square on the conveyor
- Choose between Datamax and Sato printers
- Straight tamp and swing arm options allow use in hard to reach labelling areas
- Compatible with a variety of label sizes and designs
- Adjustable applicator height

## Electrical Specification

<b>Line Voltage</b>	115VAC
<b>Power Consumption</b>	1.5A Max at 115VAC
<b>Circuit Protection</b>	EMI Protection

## Physical Specification

<b>Enclosure Size</b>	24" x 24" x 5.25"
<b>Enclosure Material</b>	Aluminum
<b>Applicator Height</b>	9"-45" (from the floor)
<b>Footprint (WxHxD)</b>	30.25" x 62.25" x 26.5"
<b>Input Air Pressure</b>	At least 60 PSI

## Communications

<b>Communication Ports</b>	2 x RS-232
----------------------------	------------

## Label Specification

<b>Label Printer</b>	Sato printer or Data-max printer available
<b>Max Label Size</b>	6" by any length
<b>Application Method</b>	Straight tamp (pictured) or swing arm

## User Interface

<b>Display</b>	5.2" x 0.8"
<b>Keypad</b>	16-key membrane

## Operating Conditions

<b>Ideal Operating Temperature</b>	14°F to 104°F (-10°C to 40°C)
------------------------------------	-------------------------------